



**UNIVERSITI PUTRA MALAYSIA**

**DESIGN OF DIRECT SEQUENCE CODE DIVISION MULTIPLE  
ACCESS (DS-CDMA) WIRELESS TRANSMITTER USING FIELD  
PROGRAMMABLE GATE ARRAY (FPGA)**

**KHALID ELTAHIR MOHAMED OSMAN**

**FK 2002 37**

**DESIGN OF DIRECT SEQUENCE CODE DIVISION MULTIPLE ACCESS  
(DS-CDMA) WIRELESS TRANSMITTER USING FIELD  
PROGRAMMABLE GATE ARRAY (FPGA)**

**By**

**KHALID ELTAHIR MOHAMED OSMAN**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,  
In Fulfilment of the Requirement for the Degree of Master of Science**

**August 2002**



### Dedicated

To you...

...Dear mother.... for making out of us the  
person who can present such a work...for doing all this with pleasure.....

To you...

.... Dear brother Amin.... the person who lead to  
success life...and taught me how to face my struggles.....

To you...

... Dear brothers, sisters, nephews and niece...  
Mohamed, Awad, Nura, Fathia, Sadia, Asma, Omima, Ahmed, Sumia, Mahmoud,  
Amna, Mohamed, lina, Dania...

To all the glory inside you...

To you...

...love...thanks...and my simple effort...

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

**DESIGN OF DIRECT SEQUENCE CODE DIVISION MULTIPLE ACCESS  
(DS-CDMA) WIRELESS TRANSMITTER USING FIELD  
PROGRAMMABLE GATE ARRAY (FPGA)**

**By**

**KHALID ELTAHIR MOHAMED OSMAN**

**August 2002**

**Chairman: Professor Borhanuddin Mohd. Ali. Ph.D.**

**Faculty: Engineering**

This thesis describes the DS-CDMA wireless transmitter design using FPGA (Field Programmable Gate Array), which has been adopted in many wireless access technologies. Four separate blocks have been designed using digital approach to form the transmitter circuit diagram using the oscillator, the PN-code generator, the Parity Check, and the BPSK modulator. The Synopsys software has been used for the design synthesis and simulation; the VHDL (Very High Speed Integrated Circuit Hardware Description Language (VHDL)) program was used for coding and FPGA for compiling and downloading the simulation in FPGA cards.

The DS-CDMA wireless transmitter was designed to transmit with data rates up to 2 Mbps. The transmitted signals were carried out with a 40 MHz carrier frequency.

VHDL files were created for each element of the wireless transmitter. Each file was simulated and synthesized using FPGA compiler II. The control block was added for timing purposes and for framing the coded data. One bit parity was added to the data frame containing 16 serial bits.

The top-level design file was initiated using VHDL for the combined elements of the DS-CDMA wireless transmitter including the control block. The results of simulated and synthesized top-level design file using FPGA compiler II were downloaded into the Xilinx XSV300 FPGA board.

This study has demonstrated the design of DS-CDMA wireless transmitter with higher data rates using FPGA. It has also improved the performance and quality of the transmitted data by including error detection and correction.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

**REKA BENTUK PENGHANTAR WAYARLES CAPAIAN KOD  
BERBILANG DIVISI-JUJUKAN TERUS (DS-CDMA) DENGAN  
MENGUNAKAN SUSUN TERTIB GET LAPANGAN BOLEH PROGRAM  
(FPGA)**

**Oleh**

**KHALID ELTAHIR MOHAMED OSMAN**

**Ogos 2002**

**Pengerusi : Profesor Borhanuddin Mohd. Ali, Ph.D.**

**Fakulti : Kejuruteraan**

Projek ini menghuraikan reka bentuk penghantar wayarles capaian kod berbilang divisi –jujukan terus (*DS-CDMA*) menggunakan susun tertib get lapangan boleh program (*FPGA*) yang telah digunakan dalam banyak teknologi capaian wayarles. Empat blok berasingan telah direka bentuk dengan pendekatan digit, menggunakan oksilator, penjana kod-PN, semakan pariti dan pemodulat BPSK untuk membentuk gambar rajah litar penghantar. Implementasi dan perisian sintesis digunakan untuk menggabungkan keseluruhan komponen. Perisian Sinopsis digunakan untuk reka bentuk dan simulasi. Program *VHDL (Very High Speed Integrated Circuit Hardware Description Language)* digunakan untuk pengkodan, dan *FPGA (Field Programmable Gate Array)* digunakan untuk kompilasi dan muat turun simulasi ke dalam kad *FPGA*.

Penghantar wayarles *DS-CDMA* direka bentuk untuk melakukan penghantaran dengan kadar data sehingga 2Mbps. Isyarat yang dihantar dilaksanakan oleh pembawa berfrekuensi 40 MHz.

Fail *VHDL* dicipta untuk setiap unsur pada penghantar wayarles. Setiap fail disimulasi dan disintesis dengan menggunakan Pengompil II *FPGA*. Blok kawalan ditambahkan bagi maksud pemasaan dan kerangkaan bagi data terkod. Satu bit pariti ditambahkan pada kerangka data yang mengandungi 16 bit sesiri.

Fail reka bentuk paras tertinggi diwujudkan dengan menggunakan *VDHL* untuk unsur-unsur (penghantar wayarles *DS-CDMA*) yang digabungkan dan termasuk blok kawalan. Hasil reka bentuk paras tertinggi tersimulat dan tersintesis yang menggunakan pengompil II *FPGA* telah dimuat turunkan ke dalam papan *FPGA* Xilina XSV300.

Kajian ini telah menunjukkan reka bentuk penghantar wayarles *DS-CDMA* dengan kadar data lebih tinggi menggunakan *FPGA*. Kajian ini juga telah memperbaiki prestasi dan kualiti data yang dihantar dengan cara memasukkan pengesanan dan pembetulan ralat . Kaedah yang disyorkan yang berasaskan pemodelan perilaku memberi keupayaan simulasi yang unggul.

## ACKNOWLEDGMENTS

Is all praise to Almighty Allah (SWT) the most Benevolent, Merciful and Compassionate, for giving me the utmost strength, patience and guidance to have this work completed.

I would like to express my most sincere gratitude and deepest appreciation to the chairman of my supervisory committee, Prof. Dr. Borhanuddin Mohd Ali, Department of Computer and Communication Systems, UPM for his invaluable contribution, inputs and careful supervision. Without his constant encouragement this thesis would have never been written.

I am indebted to the members of my supervisory committee, Dr. V. Prakash, Pn. Nor Kamariah Nordin and Pn. Ratna Kalos, Department of Computer and Communication Systems, UPM, for their encouragement, constructive suggestion and guidance.

Furthermore, I would like to acknowledge School of Graduate Studies Universiti Putra Malaysia for supporting the research and granting me a Graduate Research Assistantship through IRPA (Intensification of Research Priority Areas).

I also wish to convey my thanks to Mr. Wong Wei Siung, Lini Lee, Sreedharan, Tan Wei Sin and Mr. Gary Chin from Trans. Dist. Company for their support and help.

Thanks are also due to the staff, especially Dr. Ali Mohamed Abdalrahman and Mr. Ashraf Gasim Elseed, of Multimedia University, MMU, Dr. Sabira Khatun, Mohd





Nor, Pn. Aisha and Cik. Zura, UPM, for their help and permission to use all the facilities for the wireless lab and software.

Thanks are also due to my fellow graduate students, Zubier, Mabrouk, Angline, Mayada, Coulibaly, Michael, Pri, Sahar, Furat, Arastoo, Aduwati, Kharina, Fatin and Hisham. Undergraduate students, Huzaifah, Najib and Sujea for their hospitality and help.

Also in mind always my friend's help. I would like to thank all friends for their support and helps, specially Wagie and his wife Misoon, Abdelgalil, Hassan, Mustafa, Mansour, Dr. Adil Ali Mergani and Dr. Salah Elawad.

Words are not enough to express my heartfelt feelings to my brothers Amin, Mohamed, Awad, for their constant support and concern and motivation throughout the study period.

Lastly keeping the best for her, my beloved mother, Rogia Noraljalil, I would like to express my deepest appreciation and respect for her untiring guidance, support and sacrifices since my childhood. Her spiritual support, *do'a* and motivation inspired me to do this research. I owe a depth gratitude to her, which can never be repaid.

I certify that an Examination Committee met on 28<sup>th</sup> August 2002 to conduct the final examination of Khalid Eltahir Mohamed Osman of his Master of Science thesis entitled “Design of Direct Sequence Code Division Multiple Access (DS-CDMA) Wireless Transmitter using Field Programmable Gate Array (FPGA)” in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination committee are as follows:

**Ishak Aris, Ph.D.**

Lecturer  
Department of Electrical and  
Electronics Engineering  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**Borhanuddin Mohd. Ali, Ph.D.**


Associate Professor  
Department of Computer and  
Communication Systems  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**V. Prakash, Ph.D.**

Lecturer  
Department of Computer and  
Communication Systems  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**Ratna Kalos Zakiah**

Lecturer  
Department of Computer and  
Communication Systems  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)



---

**SHAMSHER MOHAMAD RAMADILI, PH.D.**  
Professor/Deputy Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date: **8 NOV 2002**

This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee are as follows:

**Borhanuddin Mohd. Ali, Ph.D,**

Associate Professor  
Department of Computer and  
Communication Systems  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**V. Prakash, Ph.D,**

Lecturer  
Department of Computer and  
Communication Systems  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**Ratna Kalos Zakiah**

Lecturer  
Department of Computer and  
Communication Systems  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)



---

**AINI IDERIS, Ph.D,**  
Professor/Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date: 9 JAN 2003

## DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations, which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institution.



---

Name: KHALID ELTAHIR MOHAMED OSMAN

Date: 6/11/2002

## TABLE OF CONTENTS

	<b>Page</b>
DEDICATION.....	ii
ABSTRACT.....	iii
ABSTRAK.....	v
ACKNOWLEDGMENTS.....	vii
APPROVAL SHEETS.....	ix
DECLARATION FORM .....	xi
LIST OF TABLES.....	xv
LIST OF FIGURES.....	xvi
LIST OF ABBREVIATIONS.....	xviii
<b>CHAPTER</b>	
1 INTRODUCTION.....	1
1.1 Background of the Study.....	1
1.2 Problem Statment.....	3
1.3 Significance of the Study .....	4
1.4 Objectives of the Thesis.....	4
1.5 Constraints of the Project.....	5
1.6 Thesis Organization .....	8
2 LITERATURE REVIEW.....	10
2.1 Multiple Access.....	11
2.2 Classification of CDMA .....	12
2.3 Direct Sequence CDMA .....	14
2.4 Comparison between FH-CDMA and DS-CDMA .....	16
2.5 Near-Far Interference Problems in DS-CDMA Systems.....	17
2.6 Capacity of DS-CDMA.....	17
2.7 Adaptive Power Control in DS-CDMA .....	17
2.8 Spreading and Despreading in Direct Sequence .....	19
2.9 DS-CDMA Wireless Transmitter.....	21
2.9.1 Pseudorandom Noise Sequence .....	23
2.9.2 Parity Check.....	24
2.9.3 Oscillator.....	25
2.9.4 Modulation Technique.....	26
2.9.4.1 BPSK Modulator .....	27
2.10 Antenna .....	28
2.11 DS-CDMA Wireless Transmitter Circuit Operation.....	30
2.12 System Design with the VHDL Approach.....	32
2.12.1 Overview of VHDL .....	32
2.12.2 Design Methodology.....	34
2.12.3 VHDL Modeling Structure .....	35
2.12.4 Entity and Architecture Declarations.....	36
2.12.5 Entity Port Declarations.....	37
2.12.6 Signal Declaration.....	38
2.12.7 Component Declarations.....	38
2.12.8 VHDL Synthesis .....	39

2.13	Test Bench.....	41
2.14	Field Programmable Gate Array (FPGA) .....	41
2.14.1	FPGA Compiler II .....	42
2.15	Conclusion.....	43
3	METHODOLOGY .....	44
3.1	System Implementation and Design Using VHDL.....	44
3.2	Bottom-up Approach and Directory Strategy .....	45
3.3	Project Development.....	45
3.4	Architectural Design for the Transmitter .....	46
3.4.1	PN Code Generator.....	47
3.4.2	Parity Check.....	49
3.4.3	Control Block.....	52
3.4.4	Oscillator .....	52
3.4.5	BPSK Modulator.....	53
3.5	Design Flow Chart .....	54
3.6	Simulation Steps.....	56
3.7	The Hardware Implementation .....	58
3.8	Conclusion.....	59
4	RESULTS AND DISCUSSION .....	61
4.1	The PN Generator .....	61
4.2	Control Block.....	62
4.3	The Multiplexer.....	63
4.4	16-bit Shift Register .....	63
4.5	The Parity Check.....	64
4.6	1-bit Shift Register .....	65
4.7	BPSK Modulator.....	65
4.8	The Top-level Design of (PN Generator + Oscillator + BPSK) .....	66
4.9	The Transmitter Top-level Design .....	68
4.10	The Hardware Design of the DS-CDMA Transmitter .....	72
4.11	Conclusion.....	73
5	CONCLUSIONS AND FUTURE WORK .....	75
5.1	Future Work .....	76
	REFERENCES.....	78
	APPENDICES.....	81
1	VHDL Source Code for the PN Code Generator .....	82
2	Optimized FPGA Circuit Diagrams for PN Generator .....	84
3	VHDL Source Code for the Control Block.....	85
4	The Optimized FPGA Circuit for the Control Block.....	87
5	VHDL Source Code for the Multiplexer.....	88
6	The FPGA Optimized Chip for the Multiplexer.....	89
7	VHDL Source Code for the 16-bit Shift Register.....	90
8	The Optimized FPGA Chip for the 16-bit Shift Register .....	92

9	VHDL Source Code for the Parity.....	93
10	FPGA Chip for the Parity.....	94
11	VHDL Source Code for the 1-bit Shift Register.....	95
12	The FPGA Optimized Chip for 1-bit Shift Register.....	96
13	VHDL Source Code for the BPSK Modulator.....	97
14	The Optimized FPGA Chip for the BPSK Modulator .....	100
15	VHDL Source Code for the Top-level Design for the PN Generator, Oscillator and BPSK Modulator .....	101
16	The Optimized FPGA Chip for the Top-Level Design (First simulation).....	103
17	VHDL Source Code for the Test-bench of the Top-level Design File for the PN Generator, Oscillator, and BPSK Modulator .....	104
18	VHDL Source Code for the Top-level Design of the Transmitter.....	106
19	The Optimized FPGA Chip for the top-Level Design of the Transmitter .....	108
20	The Testbench File for the Top-level Design of the Transmitter.....	109
21	Information on VSS Waveform Viewer .....	112
22	Xilinx XSV Datasheet.....	114
23	Features of XSV FPGA board.....	115
	VITAE.....	117

**LIST OF TABLES**

<b>Table</b>	<b>Page</b>
2.1 Comparison between DS and FH-CDMA.....	16
3.1 Variables for LFSR design.....	47
3.2 Truth table of the RF carrier and PN code input, and DS/SS BPSK output.....	54



## LIST OF FIGURES

Figure	Page
2.1: Global area covered by CDMA .....	10
2.2 Multiple access schemes: (a) FDMA, (b) TDMA and (c) CDMA .....	12
2.3 Classification of CDMA .....	13
2.4 Direct sequence, frequency hopping and time hopping .....	14
2.5 Block diagram of a DS-CDMA transmitter .....	15
2.6 Receiver of a DS-CDMA signal .....	15
2.7 Transmission power control in open and closed loops .....	19
2.8 Spreading DS-CDMA .....	20
2.9 Despreading in DS-CDMA .....	21
2.10 Hierarchy of transmitter design.....	23
2.11 Structural model of a digital "ring" oscillator. ....	25
2.12 PN sequence wave and DS/SS BPSK signal.....	27
2.13 SR type counter with generated clock waveform. ....	28
2.14 Conceptual diagram of BPSK modulator.....	28
2.15 (a) long-wire antenna, (b) Radiation pattern .....	30
2.16 (a) loop antenna (b) Radiation pattern (Yang (1998)) .....	30
2.17 DS-CDMA wireless transmitter circuit.....	32
2.18 (a) Traditional schematic design approach (b) VHDL-based design approach .	35
2.19 VHDL modeling structure.....	36
2.20 Flow in VHDL synthesis.....	39
2.21 High –level design flow .....	40
2.22 General purpose processing with flexible software .....	42
3.1 Flow chart of Proposed Project .....	46

3.2 Conceptual diagram of the 16-stage LFSR .....	49
3.3 Flow chart of the PN code operation.....	50
3.4 Block diagram of the parity check .....	51
3.5 17-bit data frame .....	51
3.6 Waveforms of the PN code sequence and DS/SS BPSK.....	54
3.7 Flow chart of the DS-CDMA wireless transmitter .....	55
3.8 FPGA Compiler II design flow overview .....	57
3.9 Gxsload download window for the Xilinx XSV-300 FPGA board .....	59
4.1 The input/output ports of the PN generator.....	62
4.2 The control block input and output ports.....	62
4.3 The pin connection of the multiplexer .....	63
4.4 Input ports, output ports of the 16-bit shift register .....	64
4.5 The parity check 16-bit input and 1-bit output.....	64
4.6 The pins connection of the 1-bit shift register .....	65
4.7 The BPSK modulator input and output connections.....	66
4.8 The top-level design pins connections .....	67
4.9 The waveform of the top-level design .....	67
4.10 The input, output ports of the top-level design of the transmitter.....	68
4.11 The top-level trace of the transmitter .....	69
4.12 VSS waveform represents the initialization of the transmission .....	70
4.13 Trace diagram of the transmitter showing the first transmitted bits appear from the BPSK after 17000ns.....	71
4.14 The end of 1s time simulation.....	71
4.15 The hardware design of the transmitter.....	72

**LIST OF ABBREVIATIONS**

AMPS	Advanced Mobile Phone Service
CDMA	Code Division Multiple Access
DS	Direct Sequence
FH	Frequency Hopping
FHMA	Frequency Hopping Multiple Access
FHSS	Frequency Hopping Spread Spectrum
FSK	Frequency Shift Keying
JTIDS	Join Tactical Information Distribution System
LAN	Local Area Network
LPI	Low Probability of Intercept
NMT	Nordic Mobile Telephone
PN	Pseudo-Noise
RF	Radio Frequency
SNR	Signal to Noise Ratio
SS	Spread Spectrum
SSMA	Spread Spectrum Multiple Access
TACS	Total Access Communications System
TxPC	Transmit Power Control
UPM	Universiti Putra Malaysia

## CHAPTER 1

### INTRODUCTION

#### 1.1 Background of the Study

Code Division Multiple Access (CDMA) is a radically new concept in wireless communications. It has taken cellular radio systems by storm with its potential to dramatically increase both the system capacity and service quality. CDMA is a *spread spectrum* technology in that it spreads the information from a narrowband signal over a much broader bandwidth.

One of the most important concepts to cellular telephony is *multiple access* which allows several users to be supported simultaneously. In other words, several users share a pool of channels with any user able to use any channel and no channel assigned to any user. A channel is therefore merely a part of the radio resource, temporarily allocated for a call. *Multiple access* is therefore just how a radio spectrum is divided into channels and how the channels are allocated to the several users of the system.

CDMA architecture is based on the spread-spectrum technique (Tabbane, 2000), initially developed by the military because of its usefulness in tactical environments. It is used, for instance, in GPS as part of the tactical information distribution system (JTIDS). The core principle of spread spectrum is to use noise-like carrier waves in, as the name implies, a bandwidth much wider than that required for simple point-to-point communication at the same data rate. Militarily there were two advantages – it is impossible to jam by the enemy (anti-jam, or AJ) and masks the fact that communication is taking place. Thus, in military parlance, it was called *low probability intercept* (LPI). Although first used in the early days of World War II, it was only in 1978 that spread-spectrum techniques were proposed for high capacity cellular mobile communications systems.

There are two main techniques involved - Frequency Hopping (FH) and Direct Sequence (DS). DS is also called Code Division Multiple Access (CDMA). In both techniques, synchronization of the transmitter and receiver is required. Both use a pseudo-random carrier, but the carrier is created in different ways.

Rahman (2000) recorded that the Direct Sequence Spread Spectrum (DS-SS) uses a code sequence with a bit rate higher than the digital data bit rate to be transmitted. The carrier signal is modulated by the code sequence resulting in a wideband signal from the transmitter. The process is reversed at the receiver to regenerate the data transmitted.

In CDMA, each station is allocated a random sequence or code. This sequence is unique to the station and must be orthogonal or quasi-orthogonal (i.e. decorrelated)

with all the other sequences. In FH-CDMA, the code is used to generate a unique hopping sequence. In DS-CDMA, the code is used to make a quasi-random (i.e. similar to noise) high rate transmitted signal combined with the information spread the spectrum.

A transmitter is linked to the receiver by radio waves to the allocated base station, or cable line (wired) to a computer allowing the computer to transmit/receive data from a similarly equipped remote control.

## **1.2 Problem Statement**

There are many types of electronic circuits used for transmission with different options for DS-CDMA. The use of some circuitry was dictated by the availability of a particular IC, or because a portion of a quad gate was yet unused. Some circuits using passive components also need high power to drive the circuit. The addition to the high power needed the passive circuits is altered to decrease the circuit operations of transmission, when the transmitter operates with long time duration. These effects appear as thermal heat that increases the passive components values and decrease the efficiency of transmission. However, the circuit used is easy to implement and simplify.

For these reasons, DS-CDMA wireless transmitter using FPGA is regarded as a promising technique for future CDMA networks. The transmitter is mainly used digital components such as flip-flops, gates, etc., which leads the transmission in higher performance.

### **1.3 Significance of the Study**

Wireless communications with mobile and cellular radio technology is experiencing its fastest growth ever, particularly in the past 10 years. It has already progressed from the first generation (1G) to second generation (2G) which uses Frequency Division Multiple Access (FDMA) and Time Division Multiple Access (TDMA). In the new millennium the world is about to receive the third generation, which is predicated on higher data rate and better spectrum efficiency to enable wireless data communication in full multimedia.

In 3G, the information transferred is not limited to having voices, images and digital data separately. Users will have full coverage and mobility for 144 kbps (preferably 384 kbps) and eventually up to 2 Mbps limit. With this wideband, users are able to access the information in full multimedia form, wirelessly and with better quality.

### **1.4 Objectives of the Thesis**

The objectives of this study were to:

1. Study the spread-spectrum DS-SS concept, especially the PN coding system.
2. Study BPSK modulation in the DS-SS system.
3. Implement PN coding and BPSK modulation in the DS-SS transmitter circuit using digital transmission.
4. Design, simulate and synthesize the PN coding, BPSK modulation, Oscillator and Parity Check, using the VHDL source code.

5. Create the top-level design file for the DS-CDMA wireless transmitter using the VHDL source code for PN coding, BPSK modulation, Oscillator and Parity Check, using the FPGA compiler II.
6. Download the design into a Xilinx FPGA board.

### **1.5 Constraints of the Project**

This thesis describes the DS-CDMA wireless transmitter design using FPGA. The DS-CDMA wireless transmitter is expected to transmit at data rates up to 2 Mbps with error detection and 40 MHz carrier frequency. The Synopsys package was used as the simulation and synthesis tool (FPGA compiler II and VHDL). The Synopsys package allows easy reconfiguration of the transmitter. The design steps using this software depend mainly on the design components and the system configuration. The applicability of certain frequencies depends on the system application and design scenario. For this transmitter, the frequency carrier depends on the hardware (FPGA board) and the system components of the transmitter circuit. The FPGA board has a maximum frequency of 100 MHz. Some frequency dividers had to be used as shown in Appendix 22 to slow the frequency down to below this speed. For this project, a clock of 2 MHz was used. For the simplified design, a 40 MHz speed was used with two frequency dividers, multiplying the clock speed by 2 and 10 times.

The function of any communication system is to carry information – as voice, video or digital signals. To carry the information, a band is required. To send more information, a broader band or more time is required with a trade-off between the two. Other factors are also involved – the power pushing the signal through and the



clutter (noise) in the band. Shannon's law of channel capacity relates the maximum rate of data transfer as follows:

$$Capacity = bandwidth * \log_2 \left( 1 + \frac{signalpower}{noise power} \right)$$

with capacity in bits per second, bandwidth in hertz and signal and noise powers in the same physical units, such as watts. From the equation, the relationship between capacity and bandwidth is linear. Doubling the bandwidth therefore doubles the capacity. In contrast, the effects of signal power and noise power are logarithmic and therefore less dramatic. A large increase in power will result in a less than proportionate increase in the capacity (Schweber, 1991).

The XSV board has a variety of interfaces for communicating with the outside world: parallel and serial ports, Xchecker cable, a USB port, PS/2 mouse and keyboard port and 10/100 Ethernet PHY layer interface. There are also two independent expansion ports, each with 38 general-purpose I/O pins connected directly to the Virtex FPGA. The board can be configured through the parallel port, serial port, Xchecker cable or from a bit stream stored in the 16 M bit Flash RAM. The Flash RAM can also store data for use by the FPGA after the configuration is complete. The complete features of the XSV FPGA board were discussed in Appendix 23.

To extend the project to the analog portion of the transmitter, a special version of VHDL called VHDL-AMS can be used for analog-mixed signal and might be able to be used for analog system design. However, VHDL-AMS capability has to be investigated first as a feasibility study.